

DIPLAST « C », CONVERTING



Converting examples.



Distriplast is unique in its exclusive focus on the Polypropylene (PP) corrugated sheet continuous manufacturing throughout the year. Distriplast markets a comprehensive programme for converters.

Certified ISO9001:2008 and ISO14001:2004, Distriplast is a member of Beaulieu International Group and is situated in Dunkirk (F).

A bespoke service for converters

- Diplast serie "C" PP corrugated sheets ready for converting is made from best PP quality. The converter can produce a wide range of packagings corresponding to his industrial specification requirements.
- Sheets can easily be die-cut. Folding-, gluing (corona treatment requested), ultrasound-, or hot welding may make highly sophisticated boxes.
- Diplast standard colours: translucent, white, black from 250kg; yellow, blue, green, red from 500kg. On the top of Diplast's standard colours, any RAL colour may be matched from 2 metric tons of sheets per order.
- Technical treatments: ESD, VCI, flame-retardant, antistatic, UV materials from one metric ton.



Diplast

A successful conversion

ISO 9001
BUREAU VERITAS
Certification



ISO 14001
BUREAU VERITAS
Certification



By definition, sheets aimed to be converted are designed according to your specifications. Our long know-how in corrugated sheet extrusion enables to think outside the box in optimising specific thickness-grammage ratios to match your requirements; nevertheless, tolerated technical data form some boundaries.

- Length (flute direction) : mini 0,8m, maxi 7,5m. Tolerances : $\pm 5\text{mm/m}$ ($> \pm 5\text{mm}$),
- Width: mini 0,6m, maxi 3m (2,4m for thickness $\geq 7\text{mm}$). Tolerances : $+3/-0 \text{ mm/m}$ ($\pm 1\text{flute/width}$ for thickness $\geq 7\text{mm}$),
- Squareness tolerance : Diagonal $\pm 3\text{mm/m}$ ($\pm 5\text{mm/m}$, thickness $\geq 7\text{mm}$),
- Weight tolerances $\pm 2\%$.
- Flatness tolerances $\pm 2\text{mm}$.

Packaging : On a wood pallet, PP corner protections, protection layer pad+ PE cap, + 2 PP-straps+ PE stretchable film.

Warranty : The Corona 42 Dynes treatment is guaranteed 6 months following receipt. For other treatments, ask for conditions and storage limits.

Options: Food Contact certificates, ESD, antistatic, VCI, UV protection, flame retardant.



🌱 In its environmental approach, Distriplast encourages the recycling of materials by integrating a dominating share of reground PP in other qualities of sheets. We repurchase also your cutting scraps of clean PP corrugated sheets (without another material) compacted in balls by complete truck.



🌱 DISTRIPLAST promotes multimodal transport; less time on the roads means less CO₂ rejected into the atmosphere. For its customers of the south-east of France, DISTRIPLAST takes care not to reject more CO₂ than for a regional transport.

Distriplast Flandre SAS, Z.I. Petite Synthe, BP 20106 F - 59944Dunkerque Cedex 2 | www.distriplast.com
Distriplast.flandre@bintg.com - T +33 (0)3 28 29 24 80 - F +33 (0)3 28 25 19 93
TVA FR 10349077941 - SAS au capital de 6 900 000€
RCS Dunkerque 89B7 - Siret 349 077 941 00012 - NAF 252A
BIC : NATXFRPP, IBAN : FR76 3000 7999 9904 2085 9100 077